



25 mm x 52 mm x 25 mm SKF NATR 25 X cylindrical roller bearings

Bearing No. NATR 25 X

NATR 25 X Bearing 2D drawings and 3D CAD models

| | |
|--|-------------|
| Size | 25x52x24 mm |
| Bore Diameter | 25 mm |
| Outer Diameter | 52 mm |
| Width | 24 mm |
| D | 52 mm |
| d | 25 mm |
| C | 24 mm |
| B | 25 mm |
| d ₁ | 41.5 mm |
| r _{1,2} - min. | 1 mm |
| Basic dynamic load rating - C | 14.7 kN |
| Basic static load rating - C ₀ | 25.5 kN |
| Fatigue load limit - P _u | 3.1 kN |
| Maximum static radial loads - F _r | 21.6 kN |
| Maximum static radial loads - F _{0r} | 31 kN |
| Limiting speed | 2400 r/min |
| d ₁ | 41.5 mm |
| r _{1,2} min. | 1 mm |
| Basic dynamic load rating C | 14.7 kN |
| Basic static load rating C ₀ | 25.5 kN |
| Fatigue load limit P _u | 3.1 kN |
| Maximum dynamic radial loads F _r max. | 21.6 kN |



Shandong ZXY Bearing Science & Techno...

| | |
|--|---------|
| Maximum static radial loads $F_{0r \text{ max.}}$ | 31 kN |
| Mass support roller | 0.28 kg |